

A	Dept	
	Qty	
	DC	1
	ED	1
	IE	1
	ISO	1
B	PD	1
	R&D	1
	SD	1
	QA	1
	QC	1
	QE	1

NOTES:

1. MAIN SPECIFICATIONS

- . Housing material: NYLON 66
- . Wire range: AWG#26~#16
- . Rated voltage: 300V
- . Rated current: 5A
- . Contact resistance: 30mΩ Max
- . Insulation resistance: 1000MΩ Min
- . Withstanding voltage: 500V, AC 1 minute
- . Temperature range: -25 ~ +85°C
- . Recommend PC board thickness: 1.6~2.0mm

2. PRODUCT NUMBER CODE:

Terminal:

T-DS1069-02 - X X X 0 0

- Contact Plating

- Mounting type
C: Crimp

- Terminal type

P: Male
S: Female

Housing:

I-DS1069-02 - X X X 0 X

- Housing Type

02-A: 2P Type A

03-B: 3P Type B

04-C: 4P Type C

04-D: 4P Type D

06-F: 6P Type F

- Housing Color

W: White B: Black G: Green R:Red
T: Tan Y: Yellow

T: Transparent U: Blue Yellow

– Mounting type
C: Crimp

C. Clump

- Housing type

P: Male
Q: Female

3. Female

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE		CUSTOMER	
SCALE	1:1	SHEET	1 OF 2
DRAWING NO.	C-DS1069-02-XXXXX-C		

