

The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNELY or its affiliates. Unauthorized use or modification is strictly prohibited without prior written consent from CONNELY. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any form or manner. CONNELY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.

Rev.	Description	Drawn	Checked	Approved
A	NEW RELEASE	JLZ 07/22/25'		

NOTES:
Rated voltage:600V/DC.
Withstand voltage:2200V/DC.
Rated current:100/120A.
Temp.Range:-40°C~+125°C.
Materials:
Contact: Copper Alloy,Nickel plated.
Insulator: Nylon.
Product Number Code:
DS1208-04 - X X X X

Legend:
Contact plating
N:Nickel
Housing color
B:Black
E:Orange
Connector type
F: Female
Rated current
120:120A

Recommend Panel Hole

General Tolerance	Angle Tolerance	Projection	UNIT	TITLE
X. ±0.60	X. ±5°	mm	120A Bolt Adapter	
.X ±0.38	.X ±3°	A4	SHEET SIZE	
.XX ±0.25	.XX ±2°		SERIES	DS1208-04 SERIES

Drawing Type	Customer
SCALE	1:1 SHEET 1 OF 3
Drawing No.	C-DS1208-04-XXXXXX-A

晨翔电子有限公司
CONNELY CONNELY ELECTRONIC CO. LTD

The information provided herein is from CONNPLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNPLY or its affiliates. Unauthorized use or modification is strictly prohibited without prior written consent from CONNPLY. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNPLY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 07/22/25'		

NOTES:
Rated voltage:1000V/DC.
Withstand voltage:2200V/DC.
Rated current:150/250A.
Temp.Range:-40°C~+125°C.
Materials:
Contact: Copper Alloy,Nickel plated.
Insulator: Nylon.
Product Number Code:
DS1208-04 - X X X X X

Screw type(Dim A.)
1: A=M6
2: A=M8

Contact plating
N:Nickel

Housing color
B:Black
E:Orange

Connector type
F: Female

Rated current
250:250A

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE
X.	±0.60	X.	±5°	UNITS	mm	250A Bolt Adapter
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES DS1208-04 SERIES
.XX	±0.25	.XX	±2°	晨翔电子有限公司 CONNPLY CONNPLY ELECTRONIC CO. LTD		
DRAWING TYPE		CUSTOMER				
SCALE		1:1	SHEET 2 OF 3			
DRAWING NO.		C-DS1208-04-XXXXXX-A				

(Series Image-Reference Only)

